

# Performance Properties

## RUBBER SLATE & HAMMERED CLASSIC RAISED ROUND AND SQUARE TILE

Technical Service: (800) 874-4240

GAUGE (thickness)	1/8"	3.17mm
SIZE (length and width)	35 - 11/16" x 35 - 11/16"	905mm x 905 mm
	17 - 13/16" x 17 - 13/16"	452mm x 452 mm micro squared
PROFILE & COLOR	Decorative Slate	26 colors
	Decorative Hammered	21 colors
	Classic Raised Round	16 colors
	Classic Raised Square	16 colors
	Large Square	16 colors
	Deckpoint	16 colors
ASTM F-1344-STD.	Specifications for Rubber Floor Tile	Exceeds Requirements
ASTM D - 3389	Abrasion Resistance	0.5 g (H-18 500g @ 1,000 cycles)
ASTM D - 2240	Hardness	> 85 Shore A
ASTM D - 2047	Static Coefficient of Friction	0.54 (With specified conditioner) 0.67( bare floor Surface)
ASTM D - 297	Density	1.72 g / cc
ASTM D - 412	Tensile Strength	1,000 psi
ASTM D - 412	Elongation	170%
ASTM D - 624	Tear Die	190 lbs / in.
ASTM E - 648	Critical Radiant Flux CRF (W/cm2)	<1.10 W/cm2 (NFPA 253 Class 1)
ASTM E - 662	Smoke Density	Class 1 ≤ 450
ASTM E - 84	Fire Resistance (Steiner Tunnel)	Class II
	New York State Fire Prevention Code	File in Compliance w / Article 15, part 1120
	New York City Fire Prevention Code	Accepted under section 27-348
ASTM F - 970	Static Load Modified	1,100 psi
ASTM F - 925	Chemical Resistance	Complies
ASTM F - 1514	Heat Resistance	Better than Delta E = 8.0
ASTM F - 1515	Light Aging	Better than Delta E = 8.0
Adhesive and Spread Rate	VPI 100 2 Part Epoxy Adhesive 0 VOC Content	
	Nominally 135 Sq.ft/gal but will vary due to application & substrate variables	
	ECO 560 1 Part Acrylic Adhesive 0 VOC Content	
	Nominally 135 Sq.ft/gal but will vary due to application & substrate variables	
Trowel Size	Please refer to Installation & Maintenance Instructions	
WARRANTY (See actual VPI WARRANTY for details)	10 yrs	
MAINTENANCE (See Installation & Maintenance Instructions for details)	Green Prep and Conditioner VPI Cleaner Flex Shield or Satin Flex Shield	