

# Performance Properties



## ROLLED RUBBER

Technical Service: (800) 874-4240

GAUGE (thickness)	0.080" 2.0 mm
SIZE (length and width)	60" x 50 ft approx rolls 1.5 m x 15.2 m
PROFILE & COLOR	Decorative Patterns 32 Colors
Recycled Content	Recycled post manufactured decorative chips
ASTM F - 1859 Rubber Sheet Flooring without backing	Complies Type 1
ASTM D - 3389 Abrasion Resistance	Exceeds requirements
ASTM D - 2047 Static Coefficient of Friction	Meets and exceeds ADA Guidelines
ASTM D - 624 Tear Die	190 lbs / in.
ASTM E - 648 Critical Radiant Flux CRF (W/cm2)	>0.45 Class 1
ASTM E - 662 Smoke Density	≤ 450
ASTM E - 84 Fire Resistance (Steiner Tunnel)	Class II
ASTM F - 970 Static Load Modified	Complies / Exceeds
ASTM F - 1514 Heat Resistance	Complies
ASTM F - 1515 Light Aging	Complies
Adhesive and Spread Rate	VPI 100 2 Part Epoxy Adhesive 0 VOC Content <i>Nominally 135 Sq.ft/gal but will vary due to application &amp; substrate variables</i>
	ECO 560 1 Part Acrylic Adhesive 0 VOC Content <i>Nominally 135 Sq.ft/gal but will vary due to application &amp; substrate variables</i>
Trowel Size	Please refer to Installation & Maintenance Instructions
WARRANTY (See actual VPI WARRANTY for details)	10 yrs
MAINTENANCE (See Installation & Maintenance Instructions for details)	Green Prep and Conditioner VPI Cleaner Flex Shield or Satin Flex Shield