

Performance Properties



HARSH ENVIRONMENT RUBBER

Technical Service: (800) 874-4240

GAUGE (thickness)	1/8" Stud Height 0.020"	3.17mm Stud Height 0.5mm
SIZE (length and width)	35 - 11/16" x 35 - 11/16"	905mm x 905 mm
	17 - 13/16" x 17 - 13/16"	454mm x 454 mm micro s
PROFILE & COLOR		
	Round Low Profile with	16 colors
	Chamfered Edges	
ASTM F-1344-STD.	Specifications for Rubber Floor Tile	
ASTM D - 3389	Abrasion Resistance	Exceeds Requirements (H-22 Wheel @ 100 Cycles / 1.0 Kg load)
ASTM D - 2240	Hardness	≥ 85 Shore A
ASTM D - 2047	Static Coefficient of Friction	Exceeds ADA Guidelines
ASTM D - 471	Oil & Grease Resistance	ASTM Oil #1 Excellent ASTM Oil #3 Excellent
ASTM E - 648	Critical Radiant Flux	≥ 0.45
ASTM E - 662	Smoke Density	≤ 450
ASTM E - 84	Fire Resistance (Steiner Tunnel)	Class I
Adhesive and Spread Rate	VPI 100 2 Part Epoxy Adhesive 0 VOC Content	
	<i>Nominally 135 Sq.ft/gal but will vary due to application & substrate variables</i>	
	ECO 560 1 Part Acrylic Adhesive 0 VOC Content	
Trowel Size	Please refer to Installation & Maintenance Instructions	
WARRANTY (See actual VPI WARRANTY for details)	10 yrs	
MAINTENANCE (See Installation & Maintenance Instructions for details)	Green Prep and Conditioner VPI Cleaner Flex Shield or Satin Flex Shield	

Rubber Harsh Properties 13: 03-03-13