

Performance Properties

RUBBER & VINYL WALL BASE



Technical Service: (800) 874-4240

		Vinyl Wall Base		Rubber Wall Base
GAUGE (thickness)		1/8" or .080"		1/8" only
SIZE	Length	0.125 48" or 120' rolls 0.080 48" or 160' rolls 0.080 1/8" 48" or 96' rolls (6" only)		48" or 120' rolls 48" or 96' rolls (6" only)
	Height	2-1/2" - 4" - 6"		2-1/2" - 4" - 6"
Composition		High grade resin and vinyl		High grade resin and TP rubber
ASTM 1861-08		CONFORMS		CONFORMS
UL 992 Flame Propagation		< 2.0		< 2.0
ASTM E - 648 Critical Radiant Flux		Class I (> 0.45 W/cm2)		Class I (> 0.45 W/cm2)
ASTM E - 662 Smoke Density		< 450		< 450
ASTM E - 84 Fire Resistance (Steiner Tunnel)		Class II (26 - 75)		Class II (26 - 75)
Adhesive and Spread Rate		VPI 600 Solvent Free 1 Part Latex Adhesive 0 VOC Content Nominal coverage 180-275 Lin.ft/gal. Will vary by application If applying adhesive with a cartridge gun, use a 2 hole nozzle for 2 1/2" , 3-hole nozzle for 4" and 5-hole nozzle for 6"		
Trowel Size		1/16" x 1/16" x 1/16" Square Notched		
WARRANTY		1 year workmanship and materials		
MAINTENANCE		VPI Cleaner		

* The use of any other adhesive will void VPI's warranty. ** Refer to Rubber or Vinyl Cove or Straight base outside corners

VPI Technical Service 1-800-874-4240