

# Performance Properties



## RUBBER STAIR TREADS

Technical Service: (800) 874-4240

GAUGE (thickness)			1/4"	6mm
SIZE	Length x Width	Regular Tread	12 - 3/4" x 36"	
			12 - 3/4" x 48"	
		One-Piece	12 - 3/4" x 72"	
			19 - 5/16" x 36"	
			19 - 5/16" x 48"	
			19 - 5/16" x 72"	
PROFILE & COLOR			Decorative Slate 16 colors - 1 carton minimum order	
			Decorative Hammered 16 colors - 1 carton minimum order	
			Classic Raised Round 16 colors - 1 carton minimum order	
			Classic Raised Square 16 colors - minimum production requirements	
			Harsh Environment 16 colors - minimum production requirements	
			Visually Impaired Decorative Slate 16 colors - minimum production requirements	
			Visually Impaired Decorative Hammered 16 colors - minimum production requirements	
			Visually Impaired Regular Round 16 colors - minimum production requirements	
			Visually Impaired Regular Square 16 colors - minimum production requirements	
			Visually Impaired Harsh Environment 16 colors - minimum production requirements	
ASTM	F-1344-STD.	Specifications for Rubber Floor Tile	Meets / Complies	
ASTM	D - 3389	Abrasion Resistance		
All others			0.50g	(H-18 Wheel @ 1000 Cycles / 500g load
One Piece Harsh Environment			0.45g	(H-18 Wheel @ 1000 Cycles / 500g load
ASTM	D - 2240	Hardness	> 85 Shore A	
ASTM	D - 2047	Static Coefficient of Friction	Exceeds ADA Guidelines	
ASTM	E - 648	Critical Radiant Flux	Class I	
ASTM	E - 662	Smoke Density	< 450	
ASTM	E - 84	Fire Resistance (Steiner Tunnel)	Class I	
Adhesive and Spread Rate			VPI 100 2 Part Epoxy Adhesive 0 VOC Content	
			Nominally 135 Sq.ft/gal but will vary due to application & substrate variables	
			ECO 560 1 Part Acrylic Adhesive 0 VOC Content	
			Nominally 135 Sq.ft/gal but will vary due to application & substrate variables	
Trowel Size			Please refer to Installation & Maintenance Instructions	
WARRANTY (See actual VPI WARRANTY for details)			10 yrs	
MAINTENANCE (See Installation & Maintenance Instructions for details)			Green Prep and Conditioner VPI Cleaner Flex Shield or Satin Flex Shield	