



Adhesive Quick Chart

Subfloor Applications										
	Suspended ** Concrete	On Grade ** Concrete	Below Grade Concrete **	Suspended Plywood	Metal Floors	Radiant Heated ** Concrete	AA Existing Resilient Floor	AA Existing Ceramic or Terrazzo	Wafer Chip or Particle Board	Existing Wood or Hardwood
Static Control Vinyl Flooring	VPI 160 (3) VPI 150 (1,2)	VPI 160 (3) VPI 150 (1,2)	VPI 150 (1,2)	VPI 160 (3) VPI 150 (1,2)	VPI 150 (1,2)	VPI 150 (1,2)	VPI 150 (1,2)	VPI 150 (1,2)	N/R	N/R
Premium Resilient Tile	VPI 225 (1) VPI 100 (1,2)	VPI 225 (1) VPI 100 (1,2)	VPI 100 (1,2)	VPI 225 (1) VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	N/R	N/R
Classic Round & Square, Tactile & Deckpoint Rubber Tiles	VPI 225 (1) VPI 100 (1,2)	VPI 225 (1) VPI 100 (1,2)	VPI 100 (1,2)	VPI 225 (1) VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	N/R	N/R
Decorative Slate & Hammered Rubber Tiles	VPI 225 (1) VPI 100 (1,2)	VPI 225 (1) VPI 100 (1,2)	VPI 100 (1,2)	VPI 225 (1) VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	N/R	N/R
Harsh Environment Rubber Tiles	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	N/R	N/R
Decorative SBR Rolled Rubber	VPI 225 (1) VPI 100 (1,2)	VPI 225 (1) VPI 100 (1,2)	VPI 100 (1,2)	VPI 225 (1) VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	N/R	N/R
Sports Flooring	VPI 225 (1) VPI 230 SF (1,2)	VPI 225 (1) VPI 230 SF (1,2)	VPI 230 SF (1,2)	VPI 225 (1) VPI 230 SF (1,2)	VPI 230 SF (1,2)	VPI 230 SF (1,2)	VPI 230 SF (1,2)	VPI 230 SF (1,2)	N/R	N/R
Vinyl or Rubber Wall Base	VPI 600 Solvent Free Acrylic Wall Base Adhesive - Porous Substrates (1)									
	** Concrete Substrate			Unfinished Plywood/Wood Steps	Metal Steps	Finished Wood Steps	AA Existing Ceramic or Terrazzo Steps	Wafer Chip or Particle Board Steps	Existing Resilient Covered Steps	
## Rubber Stair Treads Nosing & Risers	VPI 225 (2) VPI 100 (1,2)			VPI 225 (2) VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	N/R	N/R
## Harsh Environment Stair Treads	VPI 100 (1,2)			VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	VPI 100 (1,2)	N/R	N/R
Accessories / Transitions	VPI 180			VPI 180	VPI 180	VPI 180	VPI 180	VPI 180	N/R	N/R

NOTE: Number referenced in "()" is the recommended trowel type.

Trowel Selection:

Type (1) – 1/16" x 1/16" Square Notch with 1/16" Flats

Type (2) – 1/16" x 1/16" Half Circular with 1/32" Flats

Type (3) - 1/8" V-notch with 1/16" flats

VPI Corporation 3123 S. 9th Street, PO Box 451, Sheboygan, Wisconsin 53082-0451 USA

Phone: (920) 458-4664 - Customer Service: (800) 874-4240 - Fax: (920) 458-1368

Email: floor@vpicorp.com Website: www.vpiflooring.com

Where multiple options are indicated, selection is determined by substrate porosity - please consult Adhesives Properties Chart or installation instructions.

** - Be sure that moisture tests are conducted and that levels are acceptable according to VPI Floor Preparation Guide and installation instructions.

AA - Whereas these adhesives may be used in this application VPI will NOT warranty bond failure; VPI recommends that existing floor covering be removed, or at least, scarified.

- VPI NC-2 Nose Caulking Compound must be used with all Treads and Stair Nosing materials.

N/R - NOT Recommended