

Accessories Performance Properties

NOTICE TO INSTALLER

THIS BROCHURE CONTAINS IMPORTANT INSTALLATION AND MAINTENANCE INFORMATION, AS WELL AS CAUTIONS AND WARNINGS. PLEASE MAKE CERTAIN THESE INSTRUCTIONS ARE PLACED IN THE HANDS OF THE FLOOR OWNER. OUR WARRANTY WILL BECOME EFFECTIVE ONLY IF THESE INSTRUCTIONS ARE FOLLOWED IN EVERY RESPECT. VPI'S EXCLUSIVE WARRANTY LIMITS VPI'S LIABILITY TO REPAIR, REPLACEMENT, OR CREDIT, AT VPI'S OPTION, ON VPIFLOOR PRODUCTS FOR WHICH A CLAIM HAS BEEN MADE ACCORDING TO VPI'S CLAIM PROCEDURE. CLAIMS FOR SURFACE DEFECTS OR VARIATIONS IN COLOR OR PATTERN MUST BE MADE TO VPI PRIOR TO INSTALLATIONS OF THE MATERIAL. FOR A COMPLETE STATEMENT OF VPI'S EXCLUSIVE WARRANTY, CONTACT: VPI, CUSTOMER SERVICE, P.O. BOX 451, SHEBOYGAN, WI 53082-0451

PROPERTY	PERFORMANCE
Durometer (ASTM D 2240)	83 +/- 3 Shore A
Flame Propagation (UL 992)	< 2.0
Smoke Density Test (ASTM E 662)	< 450
Flame Spread (ASTM E 84)	Class II
Critical Radiant Flux (CRF) (ASTM E 648 or NFPA 253)	Class I (> 0.45 W/cm ²)
Chemical Resistance (ASTM F 925)	Passes
Slip Resistance (ASTM D 2047)	0.5 SCOF
Composition	Thermoplastic rubber/vinyl alloy, binders, fillers and pigments
Environmental	No lead or other toxic heavy metals
Gauge	Varies; precision control to ensure fit
Linear Feet per Carton	Inquire; usually 240
Width	Varies
Adhesive	#180 Contact Cement*
Adhesive Application	Brush; both surfaces
Adhesive Coverage	120 SF/1Gal. or Approx. 2 Cartons/1 Gal.

* *Compatibility and performance using any other adhesive cannot be guaranteed by VPI Corporation.*

Complete product information including: architect's material specifications, installation instructions and maintenance, recommended adhesives, code and regulation compliance, warranty information and more is available at www.vpiflooring.com.

VPI product samples are available upon request:

Phone: 800-874-4240 Fax: 920-458-1368 E-mail: floor@vpicorp.com Visit: www.vpiflooring.com