



Performance Properties

VPI RUBBER FLOORING

NOTICE TO INSTALLER

THIS BROCHURE CONTAINS IMPORTANT INSTALLATION AND MAINTENANCE INFORMATION, AS WELL AS CAUTIONS AND WARNINGS. PLEASE MAKE CERTAIN THESE INSTRUCTIONS ARE PLACED IN THE HANDS OF THE FLOOR OWNER. OUR WARRANTY WILL BECOME EFFECTIVE ONLY IF THESE INSTRUCTIONS ARE FOLLOWED IN EVERY RESPECT. VPI'S EXCLUSIVE WARRANTY LIMITS VPI'S LIABILITY TO REPAIR, REPLACEMENT, OR CREDIT, AT VPI'S OPTION, ON VPI FLOOR PRODUCTS FOR WHICH A CLAIM HAS BEEN MADE ACCORDING TO VPI'S CLAIM PROCEDURE. CLAIMS FOR SURFACE DEFECTS OR VARIATIONS IN COLOR OR PATTERN MUST BE MADE TO VPI PRIOR TO INSTALLATIONS OF THE MATERIAL. FOR A COMPLETE STATEMENT OF VPI'S EXCLUSIVE WARRANTY, CONTACT: VPI CORPORATION, CUSTOMER SERVICE, P.O. BOX 451, SHEBOYGAN, WI 53082-0451.

(Harsh Environment Flooring)

GAUGES	0.125" (3.17 mm) Stud Height – 0.020" (0.5 mm)	
SIZE	17-7/8" x 17-7/8" (454 mm x 454 mm) Micro-Squared™	35-13/16" x 35-13/16" (910 mm x 910 mm)
Profiles and Colors	Round low profile with chamfered edges; 16 colors	
ASTM E-648 Critical Radiant Flux CRF (W/cm ²)	<0.45	
ASTM E-662: Smoke Density	≤450	
ASTM E-84: Flame Development	Class 1	
ASTM D-471 - Oil & Grease Resistance	ASTM OIL #1: Excellent; ASTM OIL # 3: Excellent	
ASTM D-3389: Abrasion Resistance (H-22 Wheel 500g @ 1,000 cycles)	0.45	
ASTM D-2240: Hardness Shore A	≥85	
ASTM D-2047: Static Coefficient of Friction	Meets ANSI standard for ADA Guidelines	
ASTM F-925: Chemical Resistance	Excellent (Acids, Alkalis, Solvents)	
Cigarette Burn & Solder Resistance	Excellent	
Limited Wear Warranty	10 years	
VOC's (Volatile Organic Compounds)	Very Low	

Harsh Environment Stair Treads available in 36", 48" and 72" lengths.



VPI Corporation, 3123 S.9th Street, PO Box 451, Sheboygan, Wisconsin 53082-0451 U.S.A.
 Phone: (920) 458-4664 – Fax: (920) 458-1368 - Customer Service: (800) 874-4240
 Email: floor@vpiflooring.com Website: www.vpiflooring.com