

Wall Base Performance Properties

NOTICE TO INSTALLER

THIS BROCHURE CONTAINS IMPORTANT INSTALLATION AND MAINTENANCE INFORMATION, AS WELL AS CAUTIONS AND WARNINGS. PLEASE MAKE CERTAIN THESE INSTRUCTIONS ARE PLACED IN THE HANDS OF THE FLOOR OWNER. OUR WARRANTY WILL BECOME EFFECTIVE ONLY IF THESE INSTRUCTIONS ARE FOLLOWED IN EVERY RESPECT. VPI'S EXCLUSIVE WARRANTY LIMITS VPI'S LIABILITY TO REPAIR, REPLACEMENT, OR CREDIT, AT VPI'S OPTION, ON VPIFLOOR PRODUCTS FOR WHICH A CLAIM HAS BEEN MADE ACCORDING TO VPI'S CLAIM PROCEDURE. CLAIMS FOR SURFACE DEFECTS OR VARIATIONS IN COLOR OR PATTERN MUST BE MADE TO VPI PRIOR TO INSTALLATIONS OF THE MATERIAL. FOR A COMPLETE STATEMENT OF VPI'S EXCLUSIVE WARRANTY, CONTACT: VPI, CUSTOMER SERVICE, P.O. BOX 451, SHEBOYGAN, WI 53082-0451

PROPERTY	VINYL		RUBBER
TEST DATA			
ASTM 1861-02	Conforms – Type TV		Conforms – Type TP
Flame Propagation (UL 992)	< 2.0		< 2.0
Smoke Density Test (ASTM E 662)	< 450		< 450
Critical Radiant Flux (ASTM E 648 or NFPA 253)	Class I (> 0.45 W/cm ²)		Class I (> 0.45 W/cm ²)
CONSTRUCTION			
Composition	High grade resin, thermoplastic binders, fillers and pigments		High grade resin, thermoplastic binders, fillers and pigments
Gauge	1/8" **	.080"	1/8" **
Feet per Carton (1 Length = 4')	2 1/2" & 4" 6"	Lengths 120' Rolls 180' 96'	120' 96'
Height	2 1/2", 4", 6" **		2 1/2", 4", 6" **
Style	Cove or Straight Toe		Cove or Straight Toe
INSTALLATION			
Adhesive & Spread Rate	#600 Wall Base Adhesive; Covers approximately 275 linear feet of 4" base per gallon		#600 Wall Base Adhesive; Covers approximately 275 linear feet of 4" base per gallon
Trowel Size	3/32" x 3/32" triangular notch with 3/32" flats. If applying adhesive with cartridge gun, use a 2-hole nozzle for a 2 1/2", 3-hole nozzle for a 4", and a 5-hole nozzle for 6".		3/32" x 3/32" triangular notch with 3/32" flats. If applying adhesive with cartridge gun, use a 2-hole nozzle for a 2 1/2", 3-hole nozzle for a 4", and a 5-hole nozzle for 6".
Environmental	No lead, no heavy metals. Wall Base qualifies for LEED Materials & Resource Credits 4.1 & 4.2: Recycled Content (32% Pre-Consumer content). Adhesive qualifies for LEED IEQ Credit 4.1: Low-Emitting Adhesives (0VOC).		
Warranty			
One Year*			

* The use of any other adhesive will void VPI's warranty.

** Also refers to Rubber and Vinyl Cove and Straight Base outside corners.

Complete product information including: architect's material specifications, installation instructions and maintenance, recommended adhesives, code and regulation compliance, warranty information and more is available at www.vpiflooring.com.

VPI product samples are available upon request:

Phone: 800-874-4240

Fax: 920-458-1368

E-mail: floor@vpicorp.com

Visit: www.vpiflooring.com