



Performance Properties

VPI RUBBER FLOORING

NOTICE TO INSTALLER

THIS BROCHURE CONTAINS IMPORTANT INSTALLATION AND MAINTENANCE INFORMATION, AS WELL AS CAUTIONS AND WARNINGS. PLEASE MAKE CERTAIN THESE INSTRUCTIONS ARE PLACED IN THE HANDS OF THE FLOOR OWNER. OUR WARRANTY WILL BECOME EFFECTIVE ONLY IF THESE INSTRUCTIONS ARE FOLLOWED IN EVERY RESPECT. VPI'S EXCLUSIVE WARRANTY LIMITS VPI'S LIABILITY TO REPAIR, REPLACEMENT, OR CREDIT, AT VPI'S OPTION, ON VPI FLOOR PRODUCTS FOR WHICH A CLAIM HAS BEEN MADE ACCORDING TO VPI'S CLAIM PROCEDURE. CLAIMS FOR SURFACE DEFECTS OR VARIATIONS IN COLOR OR PATTERN MUST BE MADE TO VPI PRIOR TO INSTALLATIONS OF THE MATERIAL. FOR A COMPLETE STATEMENT OF VPI'S EXCLUSIVE WARRANTY, CONTACT: VPI CORPORATION, CUSTOMER SERVICE, P.O. BOX 451, SHEBOYGAN, WI 53082-0451.

(Decorative Rolled Rubber Flooring)

| | |
|---|---|
| Gauges | 0.080" (2 mm) |
| Size | 60" x 50' (1.5 m x 15.2 m) roll |
| Profiles and Colors | Paper textured look; 32 colors |
| Recycled Content | Recycled post-manufacturing decorative chips. |
| ASTM F-1859: Rubber Sheet Flooring W/O Backing | Complies - Type 1 |
| ASTM E-648 Critical Radiant Flux CRF (W/cm ²) | >0.45 – Class 1 |
| ASTM E-662: Smoke Density | ≤450 |
| ASTM E-84: Fire Resistance (Steiner Tunnel) | Class 2 |
| ASTM D-3389: Abrasion Resistance | Exceeds Requirements |
| ASTM F-970 Static Load | Complies/Exceeds |
| ASTM F-1515: Light Aging | Complies |
| ASTM F-1514: Heat Aging | Complies |
| ASTM D-2047: Static Coefficient of Friction | Meets and exceeds ADA Guidelines |
| Limited Wear Warranty | 10 years |
| Maintenance | No Wax |



VPI Corporation, 3123 S.9th Street, PO Box 451, Sheboygan, Wisconsin 53082-0451 U.S.A.
Phone: (920) 458-4664 – Fax: (920) 458-1368 - Customer Service: (800) 874-4240
Email: floor@vpiflooring.com Website: www.vpiflooring.com