



Vinyl Wall Base Specifications

GENERAL
REFERENCES A. ASTM F 1861-02: Resilient Wall Base
WARRANTY A. Provide manufacturer's warranty under provisions of Section [01700.][01740.] B. Warranty: Include one year warranty that products are free from defects in materials and workmanship.
PRODUCTS
ACCEPTABLE MANUFACTURERS A. VPI Corporation, (VPI), P.O. Box 451, Sheboygan, WI 53082-0451
FLOOR COVERING MATERIALS A. Base: [ASTM F 1861-02] VPI Vinyl Wall Base Type TV; top set, cove or straight base, [2 ½] [4] [6] inches high, [1/8] [0.080] inch thick, color [selected.] [scheduled.] B. Pricing for wall base is determined by color. Specify color.
MANUFACTURING TOLERANCES A. Precision control gauge to assure smooth surface with no high edges
ADHESIVES A. Wall Base adhesive: VPI No. 600 Acrylic Copolymer Wall Base Adhesive. 0 calculated VOCs.
EXECUTION
EXAMINATION A. Ensure contact wall surface to ½ inch below top of base is clean and free from dirt, paint, oil, grease, wall covering, old adhesives and other extraneous substances. B. Beginning of installation means acceptance of surfaces and conditions.
INSTALLATION A. Fit top set base joints tight and vertical. Install base on solid backing; adhere tightly to wall surfaces. Miter and form internal and external corners as detailed in manufacturer's installation and maintenance instructions. (www.vpiflooring.com) B. Scribe and fit to doorframes and other obstructions.
PROTECTION A. Prohibit traffic on finished floor for 48 hours after installation.
CLEANING A. Remove excess adhesive from floor, base and wall surfaces without damage, while adhesive is still wet. B. Clean floor and base surfaces.

Complete product information including: architect's material specifications, installation instructions and maintenance, recommended adhesives, code and regulation compliance, warranty information and more is available at www.vpiflooring.com.

VPI product samples are available upon request:

Phone: 800-874-4240 Fax: 920-458-1368 E-mail: floor@vpicorp.com Visit: www.vpiflooring.com