

PRT Spray Buff

DESCRIPTION

VPI PRT Spray Buff is a totally unique formulation designed to work equally well with a high or low speed machine. Never before has a buffing restorative agent been engineered to this extreme level of performance. PRT Spray Buff is a 100% active thermoplastic buffing conditioner designed to make the properly finished PRT floor - fantastically colorful and spectacularly beautiful!

Simply spray on floors while buffing with a white pad and magically remove scratches, black marks, dirt, dullness, scuff marks, and unsightly traffic lanes. PRT Spray Buff, combined with your buffer, releases deep seated soils instantly - to clean, brighten, moisturize, and polish PRT flooring to unparalleled levels. The ultimate wet look.

PRT Spray Buff has an exclusive formulation that is self-emulsifying and will never allow buildup or floor powdering. Spray buffing is considered by many to be the lowest cost, but most effective form, of floor maintenance especially when compared to the labor and material costs involved with a complete drawdown. Use with the rest of the PRT system for optimal results.

USES / BENEFITS

- Extremely economical
- 100% Active
- Highly Concentrated
- Biodegradable
- Rejuvenates & moisturizes PRT Flex Shield
- Perfect for high or low speed maintenance programs
- Accentuates color & tone
- Deep cleans locked in soil
- Simple to use ... spray & buff
- Removes scuffs & marks
- Stops floor finish powdering
- Deepens gloss and luster
- Floors look better longer
- Re-conditions floor to assure continued optimized appearance

NOT FOR USE ON VPI ESD TILE

SPECIFICATIONS

Color	Milky Green
Color Dried	Crystal Clear
Flash Point	None
Gloss	Exceptional
Active Ingredients	

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. See container and MSDS for further safety instructions.

DIRECTIONS FOR USE

- 1.) Dust mop floor with untreated or water base treated dust mop.
- 2.) Clean floor with a properly diluted solution of PRT Cleaner. Either damp mop, or use with an auto scrubber and a red pad.
- 3.) Spray a light mist of PRT Spray Buff on floor in front path of floor machine. DO NOT OVER WET!
- 4.) Using a white pad, buff out this fine mist to a deep, rich luster.
- 5.) Flip or change pad as necessary. Pad will become soiled due to deep cleaning, rejuvenating action. 6.) ** For maximum gloss and luster using PRT Spray Buff, a proper base foundation must be established on the floor. This product is outstanding for use with the landmark PRT Maintenance System!

**Slip resistance meets or exceeds (ASTM D 2047-93) James Machine 0.5 minimum.

PRT Earthtones, simply the most durable & beautiful commercial floor on the market today.....



Everywhere Toll Free: 800-874-4240

www.vpiflooring.com VPI Corporation