

## Specifications Decorative Slate & Hammered, Classic Round & Square and Harsh Environment Rubber Flooring

### ACCEPTABLE MANUFACTURERS

1. VPI Corporation 3123 South 9<sup>th</sup> Street, P.O. Box 451, Sheboygan, WI 53082-0451

### FLOOR COVERING SPECIFICATIONS

Rubber Floor Tile meets ASTM1344 standards

1. Square edge tile 17-13/16" x 17 13/16" tile and 35-11/16" x 35 11/16" tile
2. Thickness 1/8" – 0.125 (3mm)

### MANUFACTURING SPECIFICATIONS

1. See all ASTM specifications per VPI web site: [www.vpiflooring.com](http://www.vpiflooring.com)
2. Meets VPI specific performance standards without exception or deviation

### ADHESIVES SPECIFICATIONS

1. ECO 560 one part acrylic adhesive for use at or above grade
2. VPI 100 two part epoxy for use on any grade  
Note: Harsh Environment Rubber Flooring should only be installed using VPI 100 epoxy
3. Use specified trowel and roller per VPI Installation and Maintenance instructions.

### PRE-INSTALLATION SPECIFICATIONS

1. See VPI ESD Installation and Maintenance instructions for substrate requirements, conditions and specifications.

### INSTALLATION SPECIFICATIONS

1. See VPI ESD Installation and Maintenance instructions for all requirements.

### INITIAL MAINTENANCE SPECIFICATIONS

1. See VPI ESD Installation and Maintenance instructions for all requirements.



**VPI Corporation**  
3123 S. 9th Street  
P.O. Box 451  
Sheboygan, WI 53082-0451, U.S.A.  
920-458-4664 • Fax 920-458-1368  
www.vpiflooring.com

## POST INSTALLATION SPECIFICATIONS

1. ECO 560 requires 72 hours to dry before foot traffic allowed and 4-5 days before initial maintenance.
2. VPI 100 requires 72 hours to dry before foot traffic allowed and 4-5 days before initial maintenance.

## WARRANTY INFORMATION

1. 10 year warranty free from defects in workmanship and materials

Slate & Hammered, Classic Round & Square and Harsh Specs 13: 03-03-13