

Specifications ROLLED DECORATIVE RUBBER FLOORING

ACCEPTABLE MANUFACTURERS

1. VPI Corporation 3123 South 9th Street, P.O. Box 451, Sheboygan, WI 53082-0451

FLOOR COVERING SPECIFICATIONS

Rubber Floor meets pertinent ASTM1344 standards

1. Rolled sheet rubber flooring: 60 inches wide by 50 feet long
2. Thickness 0.125 - 1/8 inch (3mm) or 080 (2mm)

MANUFACTURING SPECIFICATIONS

1. See all ASTM specifications per VPI web site: www.vpiflooring.com
2. Meets VPI specific performance standards without exception or deviation

ADHESIVES SPECIFICATIONS

1. ECO 560 one part acrylic adhesive for use at or above grade
2. VPI 100 two part epoxy for use on any grade
3. Use specified trowel and roller per VPI Installation and Maintenance instructions.

PRE-INSTALLATION SPECIFICATIONS

1. See VPI ESD Installation and Maintenance instructions for substrate requirements, conditions and specifications.

INSTALLATION SPECIFICATIONS

1. See VPI ESD Installation and Maintenance instructions for all requirements.

INITIAL MAINTENANCE SPECIFICATIONS

1. See VPI ESD Installation and Maintenance instructions for all requirements.



VPI Corporation
3123 S. 9th Street
P.O. Box 451
Sheboygan, WI 53082-0451, U.S.A.
920-458-4664 • Fax 920-458-1368
www.vpiflooring.com

POST INSTALLATION SPECIFICATIONS

1. ECO 560 requires 72 hours to dry before foot traffic allowed and 4-5 days before initial maintenance.
2. VPI 100 requires 72 hours to dry before foot traffic allowed and 4-5 days before initial maintenance.

WARRANTY INFORMATION

1. 10 year warranty free from defects in workmanship and materials

Roller Rubber Specs 13: 03-03-13