

Performance Properties

RUBBER SLATE & HAMMERED CLASSIC RAISED ROUND AND SQUARE TILE

Technical Service: (800) 874-4240

GAUGE (thickness)	1/8"	3.17mm
SIZE (length and width)	35 - 11/16" x 35 - 11/16"	905mm x 905 mm
	17 - 13/16" x 17 - 13/16"	452mm x 452 mm micro squared
PROFILE & COLOR	Decorative Slate	26 colors
	Decorative Hammered	21 colors
	Classic Raised Round	16 colors
	Classic Raised Square	16 colors
	Large Square	16 colors
	Deckpoint	16 colors
ASTM F1344	Specifications for Rubber Floor Tile	Exceeds Requirements
ASTM D3389	Abrasion Resistance	0.5 g (H-18 500g @ 1,000 cycles)
ASTM D2240	Hardness	> 85 Shore A
ASTM D2047	Static Coefficient of Friction	0.54 (With specified conditioner) 0.67(bare floor Surface)
ASTM D297	Density	1.72 g / cc
ASTM D412	Tensile Strength	1,000 psi
ASTM D412	Elongation	170%
ASTM D624	Tear Die	190 lbs / in.
ASTM E648	Critical Radiant Flux CRF (W/cm ²)	≥ 0.45 W/cm² (NFPA 253 Class 1)
ASTM E84	Fire Resistance (Steiner Tunnel)	Class II
	New York State Fire Prevention Code	File in Compliance w / Article 15, part 1120
	New York City Fire Prevention Code	Accepted under section 27-348
ASTM F970	Static Load Modified	1,100 psi
ASTM F925	Chemical Resistance	Complies
ASTM F1514	Heat Resistance	Better than Delta E = 8.0
ASTM F1515	Light Aging	Better than Delta E = 8.0
Adhesive and Spread Rate	VPI 100 2 Part Epoxy Adhesive 0 VOC Content	
	<i>Nominally 135 Sq.ft/gal but will vary due to application & substrate variables</i>	
	ECO 560 1 Part Acrylic Adhesive 0 VOC Content	
	<i>Nominally 135 Sq.ft/gal but will vary due to application & substrate variables</i>	
Trowel Size	Please refer to Installation & Maintenance Instructions	
WARRANTY (See actual VPI WARRANTY for details)	10 yrs	
MAINTENANCE (See Installation & Maintenance Instructions for details)	Green Prep and Conditioner VPI Cleaner Flex Shield or Satin Flex Shield	