

# Performance Properties

## RUBBER & VINYL WALL BASE



Technical Service: (800) 874-4240

		Vinyl Wall Base	Rubber Wall Base
<b>GAUGE (thickness)</b>		1/8" or .080"	1/8" only
<b>SIZE</b>	<b>Length</b>	0.125 48" or 120' rolls 0.080 48" or 160' rolls 0.080 1/8" 48" or 96' rolls (6" only)	48" or 120' rolls 48" or 96' rolls (6" only)
	<b>Height</b>	2-1/2" - 4" - 6"	2-1/2" - 4" - 6"
<b>Composition</b>		High grade resin and vinyl	High grade resin and TP rubber
<b>ASTM F1861</b>		<b>CONFORMS</b>	<b>CONFORMS</b>
<b>UL 992</b> Flame Propagation		< 2.0	< 2.0
<b>ASTM E648</b> Critical Radiant Flux		<b>Class I (&gt; 0.45 W/cm<sup>2</sup>)</b>	<b>Class I (&gt; 0.45 W/cm<sup>2</sup>)</b>
<b>ASTM E84</b> Fire Resistance (Steiner Tunnel)		<b>Class II (26 - 75)</b>	<b>Class II (26 - 75)</b>
<b>Adhesive and Spread Rate</b>		<b>VPI 600 Solvent Free 1 Part Latex Adhesive</b> Nominal coverage approximately 75 Lin.ft/cartridge for 4" base.  If applying adhesive with a cartridge gun, use a 2 hole nozzle for 3" , 3-hole nozzle for 4" and 5-hole nozzle for 6"	
<b>Trowel Size</b>		1/16" x 1/16" x 1/16" Square Notched	
<b>WARRANTY</b>		1 year workmanship and materials	
<b>MAINTENANCE</b>		VPI Cleaner	

\* The use of any other adhesive will void VPI's warranty. \*\* Refer to Rubber or Vinyl Cove or Straight base outside corners

VPI Technical Service 1-800-874-4240