

# Performance Properties



## RUBBER STAIR TREADS

Technical Service: (800) 874-4240

<b>GAUGE (thickness)</b>		1/4"	6mm
<b>SIZE</b>	<b>Length x Width</b>	<b>Regular Tread</b>	12 - 3/4" x 36" 12 - 3/4" x 48" 12 - 3/4" x 72"
		<b>One-Piece</b>	19 - 5/16" x 36" 19 - 5/16" x 48" 19 - 5/16" x 72"
<b>PROFILE &amp; COLOR</b>		<b>Decorative Slate</b>	16 colors - 1 carton minimum order
		<b>Decorative Hammered</b>	16 colors - 1 carton minimum order
		<b>Classic Raised Round</b>	16 colors - 1 carton minimum order
		<b>Classic Raised Square</b>	16 colors - minimum production requirements
		<b>Harsh Environment</b>	16 colors - minimum production requirements
		<b>Visually Impaired Decorative Slate</b>	16 colors - minimum production requirements
		<b>Visually Impaired Decorative Hammered</b>	16 colors - minimum production requirements
		<b>Visually Impaired Regular Round</b>	16 colors - minimum production requirements
		<b>Visually Impaired Regular Square</b>	16 colors - minimum production requirements
		<b>Visually Impaired Harsh Environment</b>	16 colors - minimum production requirements
<b>ASTM F1344</b>	Specifications for Rubber Floor Tile	<b>Meets / Complies</b>	
<b>ASTM D3389</b>	Abrasion Resistance		
	All others One Piece Harsh Environment	<b>0.50g</b> <b>0.45g</b>	(H-18 Wheel @ 1000 Cycles / 500g load) (H-18 Wheel @ 1000 Cycles / 500g load)
<b>ASTM D2240</b>	Hardness	<b>&gt; 85 Shore A</b>	
<b>ASTM D2047</b>	Static Coefficient of Friction	<b>Exceeds ADA Guidelines</b>	
<b>ASTM E648</b>	Critical Radiant Flux	<b>Class I</b>	
<b>ASTM E84</b>	Fire Resistance (Steiner Tunnel)	<b>Class I</b>	
<b>Adhesive and Spread Rate</b>		<b>VPI 100 2 Part Epoxy Adhesive 0 VOC Content</b>	
		<i>Nominally 135 Sq.ft/gal but will vary due to application &amp; substrate variables</i>	
<b>Trowel Size</b>		<b>ECO 560 1 Part Acrylic Adhesive 0 VOC Content</b>	
		<i>Nominally 135 Sq.ft/gal but will vary due to application &amp; substrate variables</i>	
<b>WARRANTY (See actual VPI WARRANTY for details)</b>		<b>10 yrs</b>	
<b>MAINTENANCE (See Installation &amp; Maintenance Instructions for details)</b>		<b>Green Prep and Conditioner</b> <b>VPI Cleaner</b> <b>Flex Shield or</b> <b>Satin Flex Shield</b>	