

Performance Properties

LOW DIRT RETENTION WALL PROTECTION SYSTEM



Technical Service: (800) 874-4240

| | | Vinyl Low Dirt Retention Wall Protection System | | Rubber Low Dirt Retention Wall Protection System | |
|--|---------------|--|--|--|--|
| GAUGE (thickness) | | 1/4" | | 1/4" | |
| SIZE | Length | 0.250 x 96" 8 PCS/CTN 768 LF / CTN | | 0.250 x 96" 8 PCS/CTN 768 LF / CTN | |
| | Height | 3" - 4" - 6" | | 3" - 4" - 6" | |
| Composition | | High grade resin and vinyl | | High grade resin and TP rubber | |
| ASTM F1861 | | CONFORMS | | CONFORMS | |
| UL 992 Flame Propagation | | < 2.0 | | < 2.0 | |
| ASTM E648 Critical Radiant Flux | | Class I (> 0.45 W/cm2) | | Class I (> 0.45 W/cm2) | |
| ASTM E84 Fire Resistance (Steiner Tunnel) | | Class II (26 - 75) | | Class II (26 - 75) | |
| Adhesive and Spread Rate | | VPI 600 Solvent Free 1 Part Latex Adhesive Nominal coverage approximately 75 Lin.ft/cartridge for 4" base. If applying adhesive with a cartridge gun, use a 2 hole nozzle for 3" , 3-hole nozzle for 4" and 5-hole nozzle for 6" | | | |
| Trowel Size | | 1/16" x 1/16" x 1/16" Square Notched | | | |
| WARRANTY | | 1 year workmanship and materials | | | |
| MAINTENANCE | | VPI Cleaner | | | |

* The use of any other adhesive will void VPI's warranty. ** Refer Wall Base Instructions for practical installation.

VPI Technical Service 1-800-874-4240