

ACCEPTABLE MANUFACTURER

1. VPI Corporation, 3123 South 9th Street, P.O. Box 451, Sheboygan, WI 53082-0451

FLOOR COVERING SPECIFICATION

1. Vinyl Wall Base MEETS ASTM F-1861-02 standards
2. VPI Vinyl Wall Base Type TV, top set,
3. Cove or Straight base with sizes as follows:

Width: 2.5", 4"	Thickness: 1/8"	Lgths: 48"	PCS per CTN:	30 pcs. or 120 lf. / roll
2.5", 4"	0.080"	Lgths: 48"		30 pcs. or 160 lf. / roll

Width: 6"	1/8"	Lgths: 48"		24 pcs. or 96 lf. / roll
6"	0.080"	Lgths: 48"		24 pcs. or 96 lf. / roll

MANUFACTURING SPECIFICATIONS

1. See all ASTM specifications per VPI web site: www.vpiflooring.com
2. Meets VPI specific VOC, durability and other performance standards without exception or deviation

ADHESIVE SPECIFICATIONS

1. VPI 600 acrylic wall base adhesive.
2. Use specified trowel and roller per VPI installation and maintenance instructions.

PRE- INSTALLATION AND INSTALLATION SPECIFICATIONS

1. See VPI wall base installation and maintenance instructions for all installation requirements

POST INSTALLATION SPECIFICATIONS

1. Prohibit traffic in area for 48 hours after installation.

WARRANTY INFORMATION

1. 10 year warranty that products are free from defects in materials and workmanship.

VPI Technical Service: (800) 874-4240

Wall Base Vinyl Specs 13: 12-10-15

